



# Dell PowerEdge R620

A hyper-dense 2-socket, 1U rack server, the Dell™ PowerEdge™ R620 has a large memory footprint and impressive I/O options that make it an exceptional platform for space-sensitive environments.

Designed for exceptional performance on a wide range of applications, the Dell PowerEdge R620 rack server is an impressive general purpose platform that is perfect for data centers with space constraints. With its hyper-dense memory (up to 768GB in a 1U form factor) and powered by Intel® Xeon® E5 processors, the R620 really shines when handling virtualization, High Performance Computing (HPC), and workgroup collaboration applications.

## Accomplish more

Pack more computing power into a space-challenged data center with the PowerEdge R620, which offers an exceptionally large memory footprint along with balanced, scalable I/O capabilities, including integrated PCIe Gen3-capable expansion slots. With reliability, availability and serviceability (RAS) features like hot-swappable fans, disks, power-supply units (PSUs) and even redundant failsafe hypervisors, the R620 keeps your data center running with rock-steady reliability.

## Dense design for demanding workloads

Virtualization environments demand high memory capacity to maximize the number of virtual machines per server, and the PowerEdge R620 was designed specifically with these environments in mind. It also offers outstanding computational density for HPC application clusters by providing powerful processing capabilities in a compact form factor.

## Tailor your network fabric

The R620's network features allow you to tailor your network throughput to match your application needs, enabling added I/O performance. Dell Select Network Adapters, our flexible NIC technology, let you choose the right network fabric without using up a valuable PCI slot. You can pick speed, technology, vendor and other options, like Switch Agnostic

Partitioning (SWAP) that lets you share and manage bandwidth on 10GbE connections.

## The PowerEdge server line

The PowerEdge family is engineered with the right combination of features and performance scalability to handle tough workloads for both large and small data center environments.

The Dell OpenManage™ systems management portfolio includes Dell Remote Access Controller (iDRAC) with Lifecycle Controller. This embedded feature helps IT Administrators manage Dell servers in physical, virtual, local and remote environments, operating in-band or out-of-band, with or without a systems management software agent. OpenManage integrates and connects to third-party systems management solutions so you can maintain your single point of control and capitalize on your existing investment. OpenManage simplifies the lifecycle of deploying, updating, monitoring and maintaining your Dell PowerEdge servers.

## PowerEdge R620

- Compute density in a 1U form factor
- Optional hot-plug, front-access PCIe SSDs
- Choice of network fabric technologies
- PCIe Gen3-enabled expansion slots

Feature	PowerEdge R620 technical specification
Form factor	1U rack
Processors	Intel® Xeon® processor E5-2600 product family
Processor sockets	2
Internal interconnect	2 x Intel QuickPath Interconnect (QPI) links: 6.4 GT/s, 7.2 GT/s, 8.0 GT/s
Cache	2.5MB per core; core options: 2, 4, 6, 8
Chipset	Intel C600
Memory <sup>1</sup>	Up to 768GB (24 DIMM slots): 2GB/4GB/8GB/16GB/32GB DDR3 up to 1600MHz
I/O slots	<b>3 PCIe slots:</b> Two x16 slots with x16 bandwidth, half-height, half-length One x16 slot with x8 bandwidth, half-height, half-length (10-drive-bay configuration is available only with 3 PCIe slot option) <b>or</b> <b>2 PCIe slots:</b> One x16 slot with x16 bandwidth, full-height, 3/4 length One x16 slot with x16 bandwidth (or x8 with one processor only), half-height, half-length
RAID controller	<b>Internal controllers:</b> PERC S110 (SW RAID) PERC H310 PERC H710 PERC H710P <b>External HBAs (RAID):</b> PERC H810 <b>External HBAs (non-RAID):</b> 6Gbps SAS HBA
Drive bays	Up to ten 2.5" hot-plug SAS, SATA, or SSD or up to four hot-plug 2.5" SAS, SATA, or SSD + two PCIe SSD
Maximum internal storage <sup>1</sup>	Up to 10TB
Hard drives	<b>Hot-plug hard drive options:</b> 2.5" PCIe SSD, SAS SSD, SATA SSD, SAS (15K, 10K), nearline SAS (7.2K), SATA (7.2K) Self-encrypting drives available
Embedded NIC	Broadcom® Quad Port 1GbE BASE-T (no TOE or iSCSI offload) Intel Quad Port 1GbE BASE-T (no TOE or iSCSI offload) Intel Dual Port 10GbE BASE-T + two 1GbE (FCoE capability enabled on 10GbE ports) Broadcom Dual Port 10GbE SFP+ with two 1GbE (TOE and iSCSI offload available on 10GbE ports)
Power supply	Platinum efficiency 495W, 750W or Platinum+ efficiency 1100W power supplies Auto-ranging power supplies
Availability	High-efficiency, hot-plug, redundant power supplies; DC power supplies; hot-plug hard drives; TPM; dual internal SD support; hot-plug redundant fans; optional bezel; luggage-tag; ECC memory; interactive LCD screen; extended thermal support; ENERGY STAR® compliant; extended power range; Switch Agnostic Partitioning (SWAP)
Remote management	iDRAC7 with Lifecycle Controller iDRAC7 Express (default), iDRAC7 Enterprise (upgrade option), 8GB vFlash media (upgrade option), 16GB vFlash media (upgrade option)
Systems management	IPMI 2.0 compliant Dell OpenManage™ Essentials and Dell Management Console Dell OpenManage Power Center Dell OpenManage Connections: <ul style="list-style-type: none"> <li>• OpenManage Integration Suite for Microsoft® System Center</li> <li>• Dell plug-in for VMware® vCenter™</li> <li>• HP Operations Manager, IBM Tivoli® Netcool®, and CA Network and Systems Management</li> </ul>
Rack support	ReadyRails™ sliding rails with optional cable management arm for 4-post racks (optional adapter brackets required for threaded hole racks)
Operating systems	Microsoft® Windows Server® 2008 R2 SP1, x64 (includes Hyper-V™ v2) Microsoft Windows® HPC Server 2008 Microsoft Windows Small Business Server 2011 SUSE® Linux® Enterprise Server Red Hat® Enterprise Linux <b>Optional Embedded Hypervisors:</b> Citrix® XenServer™ VMware vSphere™ For more information on the specific versions and additions, visit <a href="http://Dell.com/OSsupport">Dell.com/OSsupport</a> .

<sup>1</sup> 1 GB means 1 billion bytes and TB equals 1 trillion bytes; actual capacity varies with preloaded material and operating environment and will be less.

## Global services and support

Dell Services can help reduce IT complexity, lower costs and eliminate inefficiencies by making IT and business solutions work harder for you. The Dell Services team takes a holistic view of your needs and designs solutions for your environment and business objectives, while leveraging proven delivery methods, local talent and in-depth domain knowledge for the lowest total cost of ownership.

## OEM-ready version available

From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit [Dell.com/OEM](http://Dell.com/OEM).

Learn more at [Dell.com/PowerEdge](http://Dell.com/PowerEdge)

